

CmCard



Article-No:
1020-01-xxx

Description

The CmCard combines WibuKey and CodeMeter in one hardware device.

- WibuBox/U+ with 16 kbyte extended memory and 10 entries for license information.

- CodeMeter Digital Rights Management system, containing a SmartCard chip including a secure memory with a minimum of 128 kbyte including about 60 kbyte available for storing more than 1000 licenses plus additional 256 MB flash memory which can be used as a removable drive. The basic idea of the revolutionary CodeMeter concept is that this memory can be used by many different vendors at the same time.

License Options are: Text (description of an entry), Unit Counter (number of runs or actually running time of a license), Activation Time (the license is valid from), Expiration Time (the license is valid until), Feature Map (up to 32 modules can be programmed in one Feature Map), Network License Quantity (concurrent use / floating licenses within one network), Protected Data (read-only data, up to 256 bytes), Extended Protected Data (128x256 bytes read-only data), Hidden Data (only readable with password; useful as secret/private encryption key, 128x256 bytes), Secret Data (non-readable; useable as secret/private encryption key, 128x256 bytes), User Data (unsecured 256 bytes), Customer Serial Number (256 bytes).

Used algorithms: 128 bit AES, TDES, SHA-256, 224 bit ECC.

The used SmartCard chip contains a random number generator according to FIPS140-1 and fulfills EAL 4+ (Common Criteria, not certified).

Technical Specifications

- **Interface:** CardBus slot, Type II
- **Data retention:** >10 years @ 100k program/erase cycles
- **Power supply:** 3,3 V, < 350 mA
- **Temperature:** 0...45 degree C, non-condensing
- **Case/Dimensions:** 86 mm x 54 mm x 5 mm
- **Weight:** 30 g

Certificates

The WibuCmCard is tested and qualified with the following standards:

■ CE-Conformity | European Certificates

Radiated Emissions According to EN 55022/2003 (DIN VDE 0878 Part22, EN 55022:1998 + A1:2000 + A2:2003.

Immunity According to EN55024 (VDE 0878 part 24): 2003-10; EN 55024:1998 + A1:2001 + A2:2003 against: Radiated Radio Frequency (RF) and electromagnetic field

Electrostatic Discharge (ESD), air discharge
Conducted Electromagnetic RF
Fast Transient Bursts

DIN EN 61000-3-2 (VDE 0838 part 2):2001-12;
EN 61000-3-2:2000

DIN EN 61000-3-3 (VDE 0838 part 3):2002-05;
EN 61000-3-3:1995 + Corr.: 1997 + A1:2001

■ International Certificates

FCC Part 15, Subpart B

VCCI 2003-04 (Japan)

All CmCards marked as ROHS are fully compliant according to EC Directives 2002/95/EC (ROHS) and 2002/96/EC (WEEE).



ROHS compliant
WEEE-Reg-No:
DE 90465365

Ordering Information

P/N 1020-01-102: CmCard 256 MByte bulk

Other variants on request.

All dimensions in millimeter.
Subject to change without
notice.



WIBU-SYSTEMS AG
Rueppurrer Strasse 52-54
D-76137 Karlsruhe
Tel: +49-721-93172-0
Fax: +49-721-93172-22
info@wibu.com
www.wibu.com

WIBU
SYSTEMS

